

## Hypoid Gear Oil GL 5 SAE 85W-140

### DESCRIPTION

Hypoid Gear Oil GL 5 SAE 85W-140 is a high-performance high-pressure gear oil manufactured from carefully selected base oils and multifunctional extreme pressure additives. It is suitable for powered transmission and axle drives – especially for heavy-duty hypoid transmissions.

### PROPERTIES

- highest pressure-absorption capability
- reduces wear
- reduces running noise
- good viscosity/temperature properties
- excellent ageing resistance
- compatible with all sealing materials

#### Specifications / Approvals

API GL 5  
ZF-TE-ML 16D, 21A  
MIL-L 2105C

### TECHNICAL DATA

Viscosity SAE class	:	85W-140	
Density at 15 °C	:	0.91	g/cm <sup>3</sup>
Viscosity at 40 °C	:	415	mm <sup>2</sup> /s
Viscosity at 100 °C	:	29.0	mm <sup>2</sup> /s
Viscosity index	:	98	
Flash point	:	214	°C
Pour point	:	-18	°C
ASTM colour number	:	6	

### APPLICATION

For heavy-duty motor vehicle transmissions, particularly with Hypoid gearing for which an API GL 5 type gear oil is specified.

### INSTRUCTIONS

When selecting, keep to the viscosity class stipulated by the transmission manufacturer. Miscible with all branded gear oils. Fully effective only when used alone.

### AVAILABLE PACK SIZE

Hypoid Gear Oil GL 5			
SAE 85W-140	20 l	Part no.	1027 D
	205 l	Part no.	1028 D

PI 10/08/11

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

