

Getriebeöl-Verlust-Stop (Gear Oil Leak Stop)

DESCRIPTION

Gear Oil Leak Stop is a special combination of active agents formulated for sealing leaky manual, auxiliary and differential transmissions. Cleans seals made from rubber or plastic and seals leaks rapidly and economically.

PROPERTIES

- reduces oil loss via leaky seals
- prevents oil spots and pollution of the environment
- protects from deficient lubrication and transmission damage
- secures optimum lubricating action and increases operational reliability
- prevents transmission oil leaking onto clutches
- compatible with commercially available gear oils
- simple and safe to use

TECHNICAL DATA

Basis	:	combination of additives
Colour	:	blue
Density at 20 °C	:	0.91 g/cm ³
Viscosity at 40 °C	:	540 mm ² /s
Flash point	:	80 °C

APPLICATION

For all manual, auxiliary and differential transmissions.
Not suitable for use in automatic transmissions.

INSTRUCTIONS

One tube is sufficient for 1 litre of gear oil. Use two tubes for large-capacity transmission cases. The product can be added at any time. For best results, add every time the oil is changed.

AVAILABLE PACK SIZE

Gear Oil Leak Stop 50 ml tube Part no. 1042

PI 01/02/01

Our information is based on thorough research and may be considered reliable, although not legally binding.

