

## Outboard Motoroil (Outboard Engine Oil)

### DESCRIPTION

Selected mineral oils with special additives which have been developed for use in high-load, water-cooled, two-stroke outboard engines with mixture or separate lubrication systems.

### PROPERTIES

- residue-free and ash-free combustion
- prevents residues forming in the combustion chamber and exhaust ports
- prevents spontaneous ignition
- reliable prevention of corrosion from acidic gases, condensates and salt-laden air
- protects against wear
- optimum lubrication due to outstanding lubricant-film stability
- for self-mixing and separate lubrication systems

#### Specifications / Approvals:

NMMA TC-W III

API TC

JASO FB

### TECHNICAL DATA

|                     |   |       |                    |
|---------------------|---|-------|--------------------|
| ASTM colour         | : | 7     |                    |
| Density at 20 °C    | : | 0.870 | g/cm <sup>3</sup>  |
| Viscosity at 40 °C  | : | 42    | mm <sup>2</sup> /s |
| Viscosity at 100 °C | : | 7.2   | mm <sup>2</sup> /s |

### APPLICATION

For use in high-load, two-stroke outboard engines with mixture or separate lubrication systems.

### INSTRUCTIONS

Use as normal for two-stroke oils for mixture and separate lubrication systems. Keep to the mixing ratios stipulated by the relevant engine manufacturer.

### AVAILABLE PACK SIZE

|                     |       |               |
|---------------------|-------|---------------|
| Outboard Engine Oil | 1 l   | Part no. 1231 |
|                     | 5 l   | Part no. 1234 |
|                     | 20 l  | Part no. 1235 |
|                     | 205 l | Part no. 1242 |

PI 03/06/05

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

