

Hypoid Gear Oil GL 5 SAE 85W-90 LS

DESCRIPTION

A high-quality motor vehicle hypoid gear oil which has been developed for use under the extreme conditions which are encountered especially in vehicles with differential transmissions with self locking. It contains special additives, which alongside outstanding EP properties, also have the capability of altering the frictional coefficient between the clutch plates in such a way as to prevent the "stick-slip" situation with the consequential judder. The product therefore satisfies the special requirements of all well-known motor vehicle manufacturers for differential transmissions with self locking.

Specifications / Approvals:

API GL 5

MIL-L-2105 D

LIQUI MOLY recommends this product for vehicles for which the following specifications are required

DAF

Volvo (axes, limited-slip differentials)

GM B 040 1010

ZF TE-ML 05C, 21C

TECHNICAL DATA

Viscosity class	: 85W-90	DIN 51512
ASTM colour	: 6.0	DIN ISO 2049
Density at 15 °C	: 0.910 g/cm ³	DIN 51757
Viscosity at 40 °C	: 190 mm ² /s	DIN 51562
Viscosity at 100 °C	: 17.6 mm ² /s	DIN 51562
Viscosity index	: 100	DIN ISO 2909
Flash point	: 220 °C	DIN ISO 2592
Pour point	: -18 °C	DIN ISO 3016

INSTRUCTIONS

The operating instructions of the vehicle and transmission manufacturers must be followed.

AVAILABLE PACK SIZE

Hypoid Gear Oil GL 5		
SAE 85W-90 LS	1 l	Part no. 1410 D-GB-I-E-P
	1 l	Part no. 8039 D-RUS-UA
	20 l	Part no. 4706 D
	60 l	Part no. 4707 D

PI 09/06/13

Our information is based on thorough research and may be considered reliable, although not legally binding.

