

Racing Chain Lube

DESCRIPTION

High-quality thermostable, extremely adherent, throw-proof synthetic lubricant compound. After the solvent has evaporated, the product leaves an extremely adherent, soft film of grease. Also suitable for O-ring chains.

PROPERTIES

- extremely good adherence
- throw-proof
- outstanding corrosion protection
- high load-carrying capacity
- cold, hot and splash water resistant
- excellent penetration action
- outstanding friction and wear reduction
- reduces chain elongation on high-performance motorbikes
- high performance only when used alone.

TECHNICAL DATA

Basis	:	Synthetic oil/additives
Colour	:	yellowish
Operating temperature range	:	-30 °C to +180 °C short term 200 °C
Water resistance at 90 °C DIN 51,807	:	0
Biodegradability CEC-L-33-A-93	:	80 %

APPLICATION

Initial and maintenance lubrication of power-transmission chains. Especially suitable for dusty, dirty and corrosive environments. Due to extremely good adherence, especially suitable for high-load, fast-running chains

INSTRUCTIONS

Carefully clean chain with solvent such as rapid cleaners. Apply by spraying. The lubricant attains its final consistency and adherence once the solvent has rapidly evaporated.

AVAILABLE PACK SIZE

Racing Chain Lube 250 ml Part no. 1508 D-GB-I-E-P

PI 03/01/09

Our information is based on thorough research and may be considered reliable, although not legally binding.

