PRODUKTINFORMATION

Racing Gear Oil
SAE 75W-90

DESCRIPTION

Fully synthetic multi-purpose SAE class 75W-90 gear oil. High-quality synthetic base oils and special additives are used in a wide range of applications for transmissions and drives.

PROPERTIES

- reduces gear-shift resistance (easier to change gear)
- high efficiency
- wide viscosity range
- excellent wear protection
- low fuel consumption
- friction-reducing properties
- significant reduction in noise
- protects from rust and corrosion

Specifications and Approvals:
API GL 5
MIL-L 2105C/D

TECHNICAL DATA

Viscosity class	: 75W-90	
Density at 15 °C	: 0.870	g/cm³
Viscosity at 40 °C	: 82	mm²/s
Viscosity at 100 °C	: 14.5	mm²/s
Viscosity index	: 185	
Flash point	: 184	°C
Pour point	: -43	°C
ASTM colour	: 2	

APPLICATION

For high-load transmissions and final drives.

INSTRUCTIONS

As stipulated for gear oil. The transmission manufacturer's instructions must be followed. Miscible with mineral-base oil residues which can remain during oil changes in transmissions and drives. Can be easily disposed of with standard used oil.
Optimum effect only when used alone.

AVAILABLE PACK SIZE

Racing Gear Oil	500 ml	Part no. 1516 D-GB-I-E-P

PI 04/03/10

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13