

Racing Scooter 2T Basic (Two-Stroke Racing Scooter Basic)

DESCRIPTION Two-Stroke Racing Scooter Basic consists of selected mineral base oils with special additives, formulated for use in air-cooled, two-stroke engines with separate or mixture lubrication.

PROPERTIES

- protects against wear and corrosion
- protects engine and exhaust system against deposits
- guarantees clean spark plug face
- self-mixing

Specifications and Approvals:

API	TC
ISO	L-EGB
JASO	FB

TECHNICAL DATA

Density at 15 °C	: 0.875	g/cm ³
Viscosity at 40 °C	: 40	mm ² /s
Viscosity at 100 °C	: 6.7	mm ² /s
Viscosity index	: 123	
Flash point	: 120	°C
Pour point	: -12	°C
Colour	: red	

APPLICATION Used especially for modern, air-cooled two-stroke motorbikes with separate and mixture lubrication. The mixture ratios stipulated by the manufacturers must be followed.

INSTRUCTIONS Mixture lubrication
Pour contents of can into fuel tank. Add fuel according to mixing ratio and mixing will follow automatically.

Separate lubrication
Pour the contents of the can into the oil tank. The oil is mixed with fuel via a metering device.

AVAILABLE PACK SIZE

Two-Stroke Racing Scooter Basic	1 l	Part no. 1619 D-GB-I-E-P
	4 l	Part no. 1237 D-GB-I-E-P
	60 l	Part no. 1633

PI 08/05/13

Our information is based on thorough research and may be considered reliable, although not legally binding.

