

## THT SHPD Engine Oil SAE 15W-40

### DESCRIPTION

Touring High Tech SHPD Engine Oil SAE 15W-40 is a multi-purpose diesel engine oil with the highest of all performance reserves which has been specially developed for the new generation of super high-performance diesel engines with and without exhaust turbocharging. It is therefore very suitable when there are long periods between oil changes and prevents "bore polishing". Liqui Moly Touring High Tech SHPD Engine Oil must not be used in petrol engines.

### PROPERTIES

- prevents bore polishing
- guarantees reliable protection against wear
- extremely long oil change intervals
- stable to ageing and viscosity stable
- outstanding detergent and dispersant effect
- suitable for all diesel engines (aspirated and turbocharged).


#### Specifications / Approvals:

API	CG-4/SJ
ACEA	E3-96 Issue4/B4-02/B3-98 Issue2/A2-96 Issue3
MB	228.3
MAN	M3275
Volvo	VDS II
Mack	EO-L
Renault	RVI RD (beantragt)

**LIQUI MOLY recommends this product for vehicles for which the following specifications are required:**

MB	229.1
----	-------

.../2



# PRODUKTI NFORMATION



-2-

## TECHNICAL DATA

SAE Viscosity class	:	15W-40	
ASTM colour	:	4	
Density at 15 °C	:	0.89	g/cm <sup>3</sup>
Viscosity at 40 °C	:	109.5	mm <sup>2</sup> /s
Viscosity at 100 °C	:	14.5	mm <sup>2</sup> /s
Viscosity index	:	139	
Flash point	:	223	°C
Pour point	:	-30	°C
Strong base number	:	11.3	mg KOH/g
Calcium	:	0.30	wt %
Magnesium	:	0.05	wt %
Zinc	:	0.13	wt %
Phosphorous	:	0.12	wt %
Nitrogen	:	0.06	wt %
Ash, Sulphate	:	1.4	g/100 g
Evaporation loss	:	11.0	wt %

## APPLICATION

Universally suitable for all diesel engines (aspirated and turbocharged).

## INSTRUCTIONS

The operating instructions of the motor vehicle and engine manufacturers must be followed.

## AVAILABLE PACK SIZE

THT SHPD Engine Oil		
SAE 15W-40	1 l	Part no. 2474
	5 l	Part no. 2475

PI 00/09/05

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

