

Touring High Tech Motoroil SHPD 20W-50

DESCRIPTION

Touring High Tech Motoroil SHPD 20W-50 is a new generation super high performance motor oil which has been specially formulated for aspirated and turbocharged diesel engines with and without charge air cooler. A high additive content guarantees optimum lubrication under all running conditions.

PROPERTIES

- Universal use for gasoline and diesel engines with and without exhaust gas turbocharging and with and without charge air cooling.
- Stable to ageing and viscosity stable
- High lubricating film stability and reliable wear protection
- Extremely low evaporation loss
- Optimum engine cleanliness and very good dispersant properties
- Mixable with all commercially available motor oils

Specifications and approvals:


API SL/CH-4
ACEA E7-04/B4-04/A3-04
Mack EO-M-Plus

LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:

MB 228.3
MAN M3275-1
VOLVO VDS-2
KHD
MTU Typ 2
Renault RD-2
Cummins 20076/20077

TECHNICAL DATA

Viscosity class : 20W-50
ASTM color number : 4.5
Density at 15 °C : 0.90 g/cm³
Viscosity at 40 °C : 154 mm²/s
 at 100 °C : 17.5 mm²/s
Viscosity index : 125
Flash point : 225 °C
Pour point : -28 °C
Total base number, TBN : 11.3 mg KOH/g



PRODUKTINFORMATION



AREAS OF APPLICATION

For aspirated and turbocharged diesel engines with and without exhaust-gas turbocharging and with and without charge air cooling.

APPLICATION

The operating materials instructions of the assembly manufacturers must be followed.

AVAILABLE PACK SIZES

Touring High Tech Motoroil
SHPD 20W-50

5 ltrs.	Part no. 2479 D-NL-F-GR-ARAB
20 ltrs.	Part no. 2480
205 ltrs.	Part no. 2481
Bulk goods	Part no. 2490

PI 05/07/13

Our information is based on thorough research and may be considered reliable, although not legally binding.

