

## Racing Synth 2T Low Smoke

### DESCRIPTION

Racing Synth 2T Low Smoke consists of selected synthetic base oils with special additives, formulated for use in two-stroke engines with separate or mixture lubrication.

### PROPERTIES

- Residue-free combustion
- Protects against wear and corrosion
- Protects engine and exhaust system against deposits
- High thermal stability
- Self mixing

#### Specifications and approvals

API TC  
ISO L-EGD  
JASO FD  
Husqvarna

### TECHNICAL DATA

Density at 15 °C	: 0.870	g/cm <sup>3</sup>
Viscosity at 40 °C	: 60	mm <sup>2</sup> /s
Viscosity at 100 °C	: 10.0	mm <sup>2</sup> /s
Flash point	: 102	°C
Pour point	: -42	°C
Viscosity index	: 153	
Color	: red	

### AREAS OF APPLICATION

For separate and mixture lubrication systems in air- and water-cooled, two-stroke engines. The mixture ratios stipulated by the manufacturers must be followed.

### APPLICATION

#### For mixture lubrication

Pour contents of can into fuel or oil tank. Add fuel according to mixture ratio and mixing will follow automatically.

#### For separate lubrication

Pour contents of can into the oil tank. Oil is mixed with fuel via a metering device.

### AVAILABLE PACK SIZES

Racing Synth 2T Low Smoke                      1 ltr.                      Part no. 2764 D-NL-F-GR-ARAB

PI 02/11/09

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

