

Speed Benzin-Zusatz (Speed Petrol Additive)

DESCRIPTION Speed Petrol Additive consists of a combination of ash-free, self-lubricating active agents which have been formulated according to the latest fuel and additive technology. This product is characterised by its outstanding cleaning and material protection properties.

PROPERTIES

- keeps fuel system clean and prevents deposits from forming
- breaks down residues in valves and the combustion chamber
- normalises fuel consumption and exhaust values
- reduces knocking tendency in the engine
- increases economy and operating reliability
- protects against corrosion throughout the fuel system
- tried and tested in turbo systems and catalytic converters
- suitable for aspirated and fuel-injection engines

TECHNICAL DATA

Basis	: additive mixture in liquid carrier	
Colour	: yellow	
Density at 15 °C	: 0.787	g/cm ³
Regulation on flammable liquids (Germany)	: A-II	
Flash point	: 42	°C
Ash	: 0.0	%

APPLICATION Speed Petrol Additive is added to the fuel of all 2-stroke and 4-stroke petrol engines for successful results. This applies to engines in motor vehicles and ships and industrial applications. As well as being used while the engine is running, Speed Petrol Additive can be used for preserving engines when laid up for long periods.

INSTRUCTIONS 1 litre is sufficient for 400 litres of petrol. 1 measuring cup (integrated in the screw cap) is sufficient for 10 litres of petrol. The product mixes with the petrol automatically.

AVAILABLE PACK SIZE

Speed Petrol Additive	1 l	Part no. 5105
-----------------------	-----	---------------

PI 01/03/01

Our information is based on thorough research and may be considered reliable, although not legally binding.

